

DST400 Overview



Programmable
by RFID /NFC
No wiring required!



Pressure switch-transmitter-display / all-in-one

Analogue output mA / V

2x PNP digital alarm outputs

Rescalable till 1:2 full scale

Display and electrical connection are independently rotatable 335° / 343°

Pixsys srl

Via Po 16, I - 30030 Mellaredo di Pianiga VE
Ph. +39 041 519 0518 • Fax +39 041 519 0027

www.pixsys.net - sales@pixsys.net



2000.42.122	DST400 - Range -1..0 Bar / Ceramic / Out 4..20 mA - 0..10 V
2000.42.100	DST400 - Range 0..1 Bar / Ceramic / Out 4..20 mA - 0..10 V
2000.42.104	DST400 - Range 0..10 Bar / Ceramic / Out 4..20 mA - 0..10 V
2000.42.106	DST400 - Range 0..25 Bar / Ceramic / Out 4..20 mA - 0..10 V
2000.42.107	DST400 - Range 0..40 Bar / Ceramic / Out 4..20 mA - 0..10 V
2000.42.108	DST400 - Range 0..100 Bar / Ceramic / Out 4..20 mA - 0..10 V
2000.43.111	DST400 - Range 0..400 Bar / Thin film on steel / Out 4..20 mA - 0..10 V