

## TEP LU TEMPERATURE TRANSMITTER / CONTROLLER

TEP LU temperature transmitter is designed for pipe strap-on installations, for heating and cooling applications. Transmitter information can be used to control other device in the HVAC system.

Temperature is measured by a Pt1000 sensor element. The sensor element resistance information is converted into a 0...10 V signal. The temperature range can be chosen at the commissioning.

TEP LU settings can be changed by using the ML-SER tool. One point field calibration of the transmitter can be executed and the temperature output can be changed to the controller function.

TEP LU transmitter can be equipped with a 3.5-digit liquid crystal display option TE-N V2. The display resolution is 0.1 °C.

Housing is made of heat resistant plastics. The bayonet cover and the terminal blocks tilted to 45° make an easy installation. Transmitter is mounted on the pipe by means of an adjustable tie.

### Range selection

0...+50 °C	*0...+100 °C	-50...+50 °C	-50...+150 °C
S1 S2	S1 S2	S1 S2	S1 S2

\* = factory setting

### Output signal

0...+50	0...+100	-50...+50	-50...+150	Signal
0 °C	0 °C	-50 °C	-50 °C	0 V
25 °C	50 °C	0 °C	50 °C	5 V
50 °C	100 °C	50 °C	150 °C	10 V



### Technical data:

supply voltage	24 Vac/dc < 1 VA (22...30Vac/dc)
sensor	Pt1000 EN 60751/B
output	0...10 Vdc < 2 mA (temperature / controller) selectable
temperature range	selectable
pipe	Ø 32...90 mm
housing	plastics (< 120 °C)
protection class	IP54, cable entry or stem down
cable entry	M16
accuracy	± 0.5 °C (at 50 °C)
ambient temperature	0...+60 °C
time constant	5 s

### Wiring:

1	supply 24 Vac/dc
2	0 V
3	output 0...10 Vdc (temperature / controller)

### Ordering guide:

Model	Product number	Description
TEP LU	1179080	strap-on temperature transmitter
TE-N V2	1170250	display module (cover)
ML-SER	1139010	transmitter commissioning tool

Products fulfill the requirements of directive 2004/108/EC and are in accordance with the standards EN61000-6-3: 2001 (Emission) and EN61000-6-2: 2001 (Immunity).